

Hydraulic pump

HY24



PUMP SPECIFICATIONS	
Capacity [m ³ /h - (USGPM)]	80 - (352)
Head [m - (ft)]	37 - (120)
Impeller diameter [mm - (in)]/type	308 - (12.3)/4 blades opened
Hose adaptor diameter [mm - (in)]	100 - (4)
Cross section diameter [mm - (in)]	25 - (1)
Weight [kg - (lbs)]	220 - (484)



HYDRAULIC MOTOR	
Motor displacement [cc - (cu in)]	20 - (1.2)
Max. oil flow rate[l/min - (USGPM)]	41 - (11)
Max. pressure [bar - (psi)]	350 - (4350)
Power [kW-HP]	24-32.5
Speed [RPM]	2000

MATERIALS	
Casing	Spheroidal cast iron EN-GJS-500-7 (EN 1563)
Motor housing	Spheroidal cast iron EN-GJS-500-7 (EN 1563)
Wear parts	High chrome EN-GJN-HV600 (XCr18) (EN 12513)
Main shaft	High tensile steel 39NiCrMo3 (AISI 9840)

SEALS / LUBRICANT	
Motor side seals	1 mechanical seal (silicon carbide in oil bath)
Impeller side seals	1 mechanical seal (silicon carbide in oil bath) + 4 lip seal (2 BUNA + 2 TPU)
Oil type	ISO 32


DIMENSIONS [mm - (in)]					
H	W	D	F	PG	H1
910	437	435	413	100	575
(36.4)	(17.5)	(17.4)	(16,5)	(4)	(23)

PERFORMANCE CURVES



We reserve the right to make changes without notice

HY24



Capacity

We reserve the right to make changes without notice